

# MAPLE - CHARACTER

## PREFINISHED NATURAL

**APPEARANCE/COLOR:** The heartwood can be darker reddish-brown to brown. The sapwood ranges from nearly white to an off-white cream color. The sapwood more commonly is used than the heartwood. All types of maple can have a broad range in color variation.

**PHOTOSENSITIVITY:** Low. Slightly ambers with age and exposure to sunlight and oxygen.

**GRAIN:** Diffuse-porous. The grain generally is straight, but may be wavy, with a fine, even texture.

**HARDNESS (JANKA):** Averages 1450 lbf

**AVERAGE DRIED WEIGHT:** 3.66 lbs per sq. ft.

**SPECIFIC GRAVITY:** Averages 0.63 (at 12% MC)

**DIMENSIONAL STABILITY IN-USE:** Average.

**INSTALLATION:** Cuts, routs, planes, and shapes well, with a moderate dulling effect on cutting edges. Responds well to bending. No known concerns with nailing, when the compressor psi is set appropriately. Glue adheres well, with no known issues.

**SAND/FINISH:** Can be challenging to sand due to its density, and requires extra caution with grit progression sequence. May require a higher grit abrasive on the final passes as sanding marks may become more apparent due to the tight grain, density, and light color of the species. The wood also may burnish easily, dulling abrasives quicker than with other species. Maple tends to stain uneven based on graining in the individual boards. Takes finishes nicely, with no known concerns.

**CHARACTER GRADING RULES:** Distinct natural variations in heartwood and sapwood coloration, along with varying natural wood characters and sound knots. Will admit the following: Unlimited open knots and open characters not exceeding 1" in diameter that will fill readily. Unlimited dark green or black spots or streaks, some with slight checks in the center, and sapwood. Sapwood may be stained, blotchy or speckled. The back side will admit: Occasional scant thickness and or waney edge if piece has sufficient bearing of full thickness to support it to the floor.

## SPECIFICATIONS

|                          |                                       |
|--------------------------|---------------------------------------|
| <b>PREFINISH</b>         | Natural                               |
| <b>SOLD</b>              | In Full Carton                        |
| <b>SHIPPING WEIGHT</b>   | 3.66 lbs per sq. ft.                  |
| <b>EDGE</b>              | 4-Sided Micro-Beveled Edge            |
| <b>INSTALLATION</b>      | Nail/Staple Down                      |
| <b>STANDARD LENGTH</b>   | Random from 1'-8'                     |
| <b>STANDARD WIDTHS</b>   | 3 1/4", 4 1/4", 5 1/4", 6 1/4"        |
| <b>AVERAGE LENGTH</b>    | 36"                                   |
| <b>THICKNESS</b>         | 3/4" Solid                            |
| <b>AVG. WASTE FACTOR</b> | 5%                                    |
| <b>FINISH TYPE</b>       | 30 Sheen Solid-Based Ceramic Urethane |

**\*DISCLAIMER:** Real wood flooring will vary in color, grain pattern, and/or texture from samples as no two boards are alike.

**SHEOGA HARDWOOD FLOORING**

15320 Burton Windsor Road,  
Middlefield, OH 44062

sheogaflooring.com 800.834.1180

**SCAN QR CODE**  
to view this species  
on our website





**HARDWOOD FLOORING**

SUSTAINABLY SOURCED, HANDCRAFTED HARDWOOD FLOORING

**MAPLE CHARACTER  
PREFINISHED NATURAL**