

MAPLE - CLEAR

PREFINISHED NATURAL

APPEARANCE/COLOR: The heartwood can be darker reddish-brown to brown. The sapwood ranges from nearly white to an off-white cream color. The sapwood more commonly is used than the heartwood. All types of maple can have a broad range in color variation.

PHOTOSENSITIVITY: Low. Slightly ambers with age and exposure to sunlight and oxygen.

GRAIN: Diffuse-porous. The grain generally is straight, but may be wavy, with a fine, even texture.

HARDNESS (JANKA): Averages 1360 lbf

AVERAGE DRIED WEIGHT: 3.66 lbs per sq. ft.

SPECIFIC GRAVITY: Averages 0.63 (at 12% MC)

DIMENSIONAL STABILITY IN-USE: Average.

INSTALLATION: Cuts, routs, planes, and shapes well, with a moderate dulling effect on cutting edges. Responds well to bending. No known concerns with nailing, when the compressor psi is set appropriately. Glue adheres well, with no known issues.

SAND/FINISH: Can be challenging to sand due to its density, and requires extra caution with grit progression sequence. May require a higher grit abrasive on the final passes as sanding marks may become more apparent due to the tight grain, density, and light color of the species. The wood also may burnish easily, dulling abrasives quicker than with other species. Maple tends to stain uneven based on graining in the individual boards. Takes finishes nicely, with no known concerns.

CLEAR GRADING RULES: Face practically free of natural wood characters but the natural color of the wood shall not be considered a defect. Face is all white (100% sapwood). Will admit the following: Limited light-colored pin knots 1/8" in diameter, birds eye, small burls, thin light brown or light green streaks. The back side will admit: Occasional scant thickness and or waney edge if piece has sufficient bearing of full thickness to support it to the floor.

SPECIFICATIONS

PREFINISH	Natural
SOLD	In Full Carton
SHIPPING WEIGHT	3.66 lbs per sq. ft.
EDGE	4-Sided Micro-Beveled Edge
INSTALLATION	Nail/Staple Down
STANDARD LENGTH	Random from 1'-8'
STANDARD WIDTHS	3 1/4", 4 1/4", 5 1/4"
AVERAGE LENGTH	42"
THICKNESS	3/4" Solid
AVG. WASTE FACTOR	5%
FINISH TYPE	30 Sheen Solid-Based Ceramic Urethane

***DISCLAIMER:** Real wood flooring will vary in color, grain pattern, and/or texture from samples as no two boards are alike.

SHEOGA HARDWOOD FLOORING

15320 Burton Windsor Road,
Middlefield, OH 44062

sheogaflooring.com 800.834.1180

SCAN QR CODE
to view this species
on our website





HARDWOOD FLOORING
SUSTAINABLY SOURCED, HANDCRAFTED HARDWOOD FLOORING

**MAPLE CLEAR
PREFINISHED NATURAL**