

# CHERRY - CLEAR

## UNFINISHED

**APPEARANCE/COLOR:** The heartwood ranges from a light pinkish-red to a reddish-brown color. The sapwood can be light brown to pale yellowish tone. Dark streaks are common. Boards can vary greatly in grain and color.

**PHOTOSENSITIVITY:** High. Darkens to a deep reddish-brown with age and exposure to sunlight and oxygen. Color change is drastic within the first 90 days after exposure to light. After 90 days, the darkening process will slow, but like all woods, it will never stop completely.

**GRAIN:** Semi-ring-porous to diffuse-porous. The grain normally is straight, with a fine and uniform texture. The texture is satiny, with some gum pockets. There can be a great variety of color, and curly or wavy figure within the species.

**HARDNESS (JANKA):** Averages 950 lbf

**AVERAGE DRIED WEIGHT:** 2.91 lbs per sq. ft.

**SPECIFIC GRAVITY:** Averages 0.50 (at 12% MC)

**DIMENSIONAL STABILITY IN-USE:** Average.

**INSTALLATION:** Cuts, routs, planes, and shapes well, with virtually no dulling effect on cutting edges. Responds well to bending. Non known concerns with nailing, when the compressor psi is set appropriately. Glue adheres well, with no known issues.

**SAND/FINISH:** Sands very easily following the standard grit progression sequence. A softer species that can show sander marks more than other species. Reduce the drum pressure on the belt sander to avoid removal of too much material on each pass. May require a higher grit abrasive on the final passes than with other species. Accepts stains well, but can appear uneven based on graining in the individual boards. Takes finished nicely, with no known concerns.

**CLEAR GRADING RULES:** Natural heartwood color variations and a small amount of sapwood, along with some allowable natural wood characters. Will admit the following: Occasional pin knots (1/4" in diameter), small burls, streaks, gum pockets.

## SPECIFICATIONS

<b>SOLD</b>	In full bundles
<b>SHIPPING WEIGHT</b>	2.91 lbs per sq. ft.
<b>EDGE</b>	Square Edge, Beveled Edge (Micro Bevel or V-Groove)
<b>INSTALLATION</b>	Nail/Staple Down, Glue Assist, Glue Down (Engineered Only)
<b>STANDARD LENGTH</b>	Random from 1'-8'
<b>STANDARD WIDTHS</b>	Solid: 2 1/4", 3 1/4", 4 1/4", 5 1/4", 6 1/4", 7 1/4", 8 1/4" Engineered: 3 1/4", 4 1/4", 5 1/4", 6 1/4", 7 1/4", 8 1/4"
<b>AVERAGE LENGTH</b>	42"
<b>THICKNESS</b>	3/4" Solid or 3/4" Engineered
<b>AVG. WASTE FACTOR</b>	5%
<b>FINISH TYPE</b>	Unfinished

\*DISCLAIMER: Real wood flooring will vary in color, grain pattern, and/or texture from samples as no two boards are alike.

**SHEOGA HARDWOOD FLOORING**  
15320 Burton Windsor Road,  
Middlefield, OH 44062  
sheogaflooring.com 800.834.1180

**SCAN QR CODE**  
to view this species  
on our website





**HARDWOOD FLOORING**

SUSTAINABLY SOURCED, HANDCRAFTED HARDWOOD FLOORING

# CHERRY CLEAR UNFINISHED