

# HICKORY - CLEAR

## PREFINISHED BUCKEYE

**APPEARANCE/COLOR:** The heartwood is tan or reddish. The sapwood is white to cream, with fine brown lines. Heartwood and sapwood often are sharply demarcated. The color can vary significantly.

**PHOTOSENSITIVITY:** Low. Slightly ambers with age and exposure to prolonged sunlight and oxygen.

**GRAIN:** Ring-porous. The grain is closed, with moderate definition. The grain can be somewhat rough-textured.

**HARDNESS (JANKA):** Averages 1820 lbf

**AVERAGE DRIED WEIGHT:** 4.16 lbs per sq. ft.

**SPECIFIC GRAVITY:** Averages 0.72 (at 12% MC)

**DIMENSIONAL STABILITY IN-USE:** Below average.

**INSTALLATION:** Cuts, routs, planes, and shapes well, with only a slight dulling effect on cutting edges. The irregular grain can chip or tear when blades become dull. Can be somewhat brittle and has a tendency to split the tongues when nailing, but can be avoided when compressor psi is set appropriately. Glue adheres well, with no known issues.

**SAND/FINISH:** Sands satisfactorily when following the standard grit progression sequence. It may require a higher grit abrasive on the final passes than with other species to minimize visible scratches. Accepts stains and finishes very nicely, with no known concerns.

**CLEAR GRADING RULES:** Natural variations in heartwood and sapwood coloration, along with some allowable natural wood characters. Will admit the following: Occasional pin knots (1/4" in diameter), small burls, streaks.

## SPECIFICATIONS

|                          |                                       |
|--------------------------|---------------------------------------|
| <b>PREFINISH</b>         | Buckeye                               |
| <b>SOLD</b>              | In Full Carton                        |
| <b>SHIPPING WEIGHT</b>   | 4.16 lbs per sq. ft.                  |
| <b>EDGE</b>              | 4-Sided Micro-Beveled Edge            |
| <b>INSTALLATION</b>      | Nail/Staple Down                      |
| <b>STANDARD LENGTH</b>   | Random from 1'-8"                     |
| <b>STANDARD WIDTHS</b>   | 3 1/4", 4 1/4", 5 1/4"                |
| <b>AVERAGE LENGTH</b>    | 42"                                   |
| <b>THICKNESS</b>         | 3/4" Solid                            |
| <b>AVG. WASTE FACTOR</b> | 5%                                    |
| <b>FINISH TYPE</b>       | 30 Sheen Solid-Based Ceramic Urethane |

**\*DISCLAIMER:** Real wood flooring will vary in color, grain pattern, and/or texture from samples as no two boards are alike.

**SHEOGA HARDWOOD FLOORING**  
15320 Burton Windsor Road,  
Middlefield, OH 44062  
sheogaflooring.com 800.834.1180

**SCAN QR CODE**  
to view this species  
on our website





**HARDWOOD FLOORING**

SUSTAINABLY SOURCED, HANDCRAFTED HARDWOOD FLOORING

**HICKORY CLEAR  
PREFINISHED BUCKEYE**